




## S220B

## Complex Structure Country Series

## INFORMATION ABOUT PRODUCT

Adiation of Co. sec.	700 - 500 - 200
Minimum Space	720x520x320 cm
Impact Protection net	27,90 m <sup>2</sup>
Dimensions	220x370 cm
Overall Height	320 cm
Free falling height	95 cm
Foundations	8 pcs
Availability of spare parts	YES
Product complies with EN 1176	YES
Age range	1,5-14
Amount of users	10



## **MATERIALS**

- Posts: Laminated pine wood 95x95mm
- Post cups made of Fiber Reinforced Plastic
- Floors: HPL Antiskid 12mm (EXT)
- Panels: HPL 12mm (EXT)
- Slide Side Panels / Panels that experience forces: HPL 18mm (EXT)
- Sliding Surface: GFRP (Glass Fiber Reinforced Polyester) t=4.5mm
- Wooden elements: Pine wood
- Wooden rungs: Exotic Hard Wood
- Metal Parts (colored): Hot Dip Galvanized and powder coated Steel
- Metal Parts (non colored): Hot Dip Galvanized (plain) or Stainless Steel (304 / 316L)
- Steel Ropes apparatus: Steel core ropes braided with polypropylene (Ø16mm). Solid and aesthetic connectors made of injection molded durable plastic / end-connectors and sleeves made of durable aluminum alloy.
- All other plastic elements: Fiber reinforced plastic
- Transparent Parts: Clear Polycarbonate material (t=5mm)
- Fasteners: Electroplated coated or Stainless Steel (304 / 316L)
- Moveable steps: Aluminum covered with EPDM rubber
- Chains: Hot Dip Galvanized (plain) or Stainless Steel (304 / 316L) / Ø6mm / According to DIN 766
- Plastic Tunnel: Co-Extruded stabilized HDPE, consisting of two walls (one corrugated exterior and one smooth interior)
  / SN 8 Stiffness / According to EN 13476-3

Please note that the above list of materials concerns the articles of the whole series. Therefore, some of them are not used in the described article.





